innowater

SALT WATER CHLORINATION IN YOUR SWIMMING POOL

Display:
pH -0.44 RETARDO
21 min   INICIO

ON/OFF
MENU
OK

INNOWATER pH BASIC

pH standalone regulator for private pools

✓ Integrated dosing pump.

✓ Interchangeable transparent peristaltic pump head without studs.

✓ Variable speed motor.

✓ Continuous and proportional dosing.

✓ LCD display with user-friendly menu system and easy calibration.

✓ Programmable dosing alarm and start delay.

✓ Wireless control output for Innowater systems (optional).

✓ Modbus communication (optional).

Included elements :

✓ Control box with integrated peristaltic pump.

✓ pH probe.

✓ Acid suction hose.

✓ Acid injection hose.

✓ Filter-suction weight.

✓ Injection fitting.

✓ Probe holder.

✓ Clamp saddles (2) for 50 mm pipe.

✓ pH4 and pH7 calibration solutions.

TECHNICAL CHARACTERISTICS

pH scale	0 - 14
pH resolution	0.01
Probe connector	BNC
pH calibration	Twp points pH 4 y pH 7
Pump regulation	Variable speed
Max. flow rate	1,5 l/h a 1,5 bar
Max. suction height (m)	1,5
Peristaltic tube	Santoprene ®
Suction hose(mm)	PVC crystal 4 x 6
Injection hose (mm)	PP 4 x 6
Supply voltaje	100 – 240 VAC, 50 – 60 Hz
Power consumption (W)	20
Weight (g)	300
Packaging dimensions (mm)	220 x 130 x 85